Marley Industrial Products

INDUSTRIAL AIR CIRCULATOR



30ACH fan head shown with optional 2430PB pole and base.

Available in two styles:

- Assembled head (motor-blade-guard) in one UPS-able carton optional mount in separate UPS-able carton.
- Assembled head (motor/blade/guard) and mount in one UPS-able box.

Fan Performance

Blade Size	Fan Head	Max Amps	CFM High	CFM Low
20”	20ACHA	1.4	3500	2900
24”	24ACH	2.2	7,000	5,900
30”	30ACH	2.5	8,200	6,200

Motor	2-speed 1/4 HP 1Ø 120 volt ball bearing totally enclosed permanently lubricated permanent split capacitor
Switch	Pull chain
Cord	12’ long 3 conductor SJT type
Blade	Coated steel
Guard	Double locking powder coat finish
Fan Head Tilt	Pedestal - 10° down or 28° up Wall mount - 40° down or 0° up
Column Adjustment	48-7/8 to 60 inches
Pedestal base	27” diameter steel dome
Column/Base Connect	5 carriage bolts

Meets OSHA standards / 1 year limited warranty.
MEP recommends the use of safety cable model 2430SC with this fan when mounted on a wall, I-beam, ceiling, or suspension mount.
Safety cable included with I-beam, ceiling and suspension mounts.

Assembled Head Ordering Summary

BLADE SIZE	FAN TYPE	ORDER NUMBER FAN HEAD	SHIPPING WEIGHT HEAD
20”	Head	**20ACHA**	51 lbs.
24”	Head	**24ACH**	51 lbs.
30”	Head	**30ACH**	51 lbs.

Mount Ordering Summary

ORDER NUMBER	DESCRIPTION	SHIP WT
2430PB	Adjustable Pedestal	35
2430WG	Wall Mount	5
2430I	I-Beam Mount	8
2430C	Ceiling Mount	7
2430S	Suspension Mount	3

Assembled Head Uni-pack Ordering Summary

BLADE SIZE	FAN TYPE	UNIPACK ORDER#	SHIPPING WEIGHT
24”	Pedestal Fan	**24ACHP**	73 lbs.
24”	Wall Mount Fan	**24ACHW**	42 lbs.
30”	Pedestal Fan	**30ACHP**	78 lbs.
30”	Wall Mount	**30ACHW**	47 lbs.

Optional Accessories

TYPE	ORDER NUMBER
Wheel Kit	**PBWK**
Safety Cable	**2430SC**