20ACHA - 24ACH - 30ACH

PROJECT	ENGINEER	SUBMITTED BY
DATE	ARCHITECT	
SHEET OF	CONTRACTOR	













SPECIFICATIONS

- ☐ 20", 24" and 30" diameter.
- ☐ 2 Speed, 1/4 HP, single phase, 120 volt, totally enclosed, permanently lubricated ball bearings, built-in thermal overload protection, permanent split capacitor motor with pull chain switch.
- ☐ Exterior switch and capacitor box for easy service.
- ☐ Precision balanced aluminum blades.
- ☐ Powder paint coated guards meeting OSHA safety standards.
- ☐ cULus listed.
- ☐ Meets federal OSHA standards.

Pedestal and wall mount Uni-Packs available.

OPTIONAL MOUNTS

- ☐ Wall*
- ☐ Adjustable Pedestal
- ☐ 27" Round Base
- ☐ Ceiling*
- ☐ I-Beam*
- ☐ Suspension Mount*

*All wall, ceiling and I-beam mounts come with Secondary Support Cable.

c UL US

ITEM	QTY	MARK	MODEL NUMBER	BLADE SIZE	FAN STYLE	CFM		RPM		MOTOR H.P.	MAX AMPS	REMARKS
						HI	LOW	HI	LOW			

INDUSTRIAL SERIES AIR CIRCULATOR *SUBMITTAL SHEET*