Marley Industrial Products

INDUSTRIAL OSCILLATING AIR CIRCULATOR



30ACHO shown with optional 2430PB pole and base.

- Oscillates in 90˚ arc or can be locked in fixed position
- Available in two styles:
  - Assembled head (motor-blade-guard) in one UPS-able carton optional mount in separate UPS-able carton.
  - Unassembled uni-pack all components (motor, blade, guards and mount) in one UPS-able carton.
- Not to be used with: I-Beam Mount (2430I), Ceiling Mount (2430C), Suspension Mount (2430S)

Fan Performance

Blade Size	Fan Head	Max Amps	CFM High	CFM Low
24”	24ACHO	2.2	7,000	5,900
30”	30ACHO	2.5	8,200	6,200

Motor	2-speed 1/4 HP 1Ø 115 volt ball bearing totally enclosed permanently lubricated permanent split capacitor
Switch	Pull chain
Cord	12’ long 3 conductor SJT type
Blade	30” unit - 3 Blade - Coated Steel 24” unit - 3 Blade - Coated Steel
Guard	Double locking powder coat finish
Fan Head Tilt	pedestal - 10° down or up wall mount - 10° down or up
Column Adjustment	48-7/8 to 60 inches
Pedestal base	27” diameter steel dome
Column/Base Connect	5 carriage bolts

Meets OSHA standards / 1 year limited warranty

MEP recommends the use of safety cable model 2430SC with this fan when mounted on a wall mount bracket.

Ordering Summary

BLADE SIZE	FAN TYPE	ORDER NUMBER FAN HEAD	ORDER NUMBER MOUNT	SHIPPING WEIGHT HEAD	SHIPPING WEIGHT MOUNT
24”	Head	**24ACHO**	**—**	40 lbs.	—
24”	Pedestal	**24ACHO**	**2430PB**	40 lbs.	35 lbs.
24”	Wall Mount	**24ACHO**	**2430WG**	40 lbs.	5 lbs.
30”	Head	**30ACHO**	**—**	47 lbs.	—
30”	Pedestal	**30ACHO**	**2430PB**	47 lbs.	35 lbs.
30”	Wall Mount	**30ACHO**	**2430WG**	47 lbs.	5 lbs.

Unassembled Uni-pack Ordering Summary

BLADE SIZE	FAN TYPE	UNIPACK ORDER#	SHIPPING WEIGHT
24”	Pedestal Fan	**24ACPOU**	73 lbs.
24”	Wall Mount Fan	**24ACWOU**	42 lbs.
30”	Pedestal Fan	**30ACPOU**	78 lbs.
30”	Wall Mount	**30ACWOU**	47 lbs.

Optional Accessories

TYPE	ORDER NUMBER
Wheel Kit	**PBWK**
Safety Cable	**2430SC**