


LEADING EDGE®
A Marley Engineered Products Brand


AF30H


PROJECT	ENGINEER	SUBMITTED BY
DATE	ARCHITECT	
SHEET OF	CONTRACTOR	













SPECIFICATIONS

- ☐ 30" diameter.
- ☐ 2 Speed, 1/3 HP, single phase, 120 volt, totally enclosed, permanently lubricated ball bearings, built-in thermal overload protection, permanent split capacitor motor with 2-speed, Drop-Cord switch.
- ☐ Precision balanced aluminum blades.
- ☐ Safety yellow powder paint coated motor, guards and mounts.
- ☐ Meets federal OSHA standards.
- ☐ Hindged Guards swing open for easy cleaning.

OPTIONAL MOUNTS

- ☐ Wall*
- ☐ Adjustable Pedestal
- ☐ 27" Round Base
- ☐ Ceiling*
- ☐ I-Beam*
- ☐ Suspension Mount*

*All wall, ceiling and I-beam mounts come with Secondary Support Cable.

ITEM	QTY	MARK	MODEL NUMBER	BLADE SIZE	FAN STYLE	CFM		RPM		MOTOR H.P.	MAX AMPS	REMARKS
						HI	LOW	HI	LOW			

SAFETY YELLOW HIGH PERFORMANCE AIR CIRCULATOR SUBMITTAL SHEET