BKOC SERIES
Commercial Baseboard Heater





Ideal Spaces:

Bedrooms
Living/Family Room
Kitchens
Bathrooms
Basements
Offices
Conference Rooms
Hallways
Waiting Rooms

Beige

- Ideal for basic, zoned primary/secondary heating
- No fans; convection heat minimizes air flow, reducing flow of bacteria and dust
- Commercial-grade 18-gauge cold rolled front cover and brackets allow heater to withstand rigors of commercial applications
- Steel-sheathed heating element combines the durability of a steel tubular heater with the excellent heat transfer characteristics of aluminum fins
- Built-in wire-way facilitates end-to-end installation of continuous-run heaters
- Large, pre-wired junction boxes at each end are provided with knockouts in the rear, bottom, inside and outside
- High temperature safety limit for added protection in case of airflow blockage
- Pre-notched marks for mounting guide
- UL-listed for installation flush to any wall and flat on any floor type
- Chimney-fin element designed for maximum air circulation
- Air flow directed away from walls to help prevent wall streaking

c UL us

10 YEAR WARRANTY ELEMENT

1 YEAR WARRANTY WORKMANSHIP

BKOC SERIES
Commercial Baseboard Heater

Scan the QR code to access additional specs and features

Models & Specifications:

	ITEM INFORMATION		ELECTRICAL DATA			DIMENSIONAL DATA	
	CATALOG NO.	UPC	VOLTS	WATTS	AMPS	LENGTH	SHIP WT.
●	BKOC25126W	685360010090	120	500	4.2	30″	7.8 lbs
●	BKOC25026W	685360009858	208	500	2.4		
●	BKOC25426W	685360010366	240/208	500/376	2.1/1.8		
●	BKOC25726W	685360010670	277/240/208	500/376/282	1.8/1.6/1.4		
●	BKOC2513W	685360010137	120	750	6.5	36″	9.0 lbs
●	BKOC2503W	685360009896	208	750	3.6		
●	BKOC2543W	685360010403	240/208	750/564	3.1/2.7		
●	BKOC2573W	685360010717	277/240/208	750/564/423	2.7/2.4/2.0		
●	BKOC2514W	685360010175	120	1000	8.3	48″	11.5 lbs
●	BKOC2504W	685360009933	208	1000	4.8		
●	BKOC2544W	685360010441	240/208	1000/752	4.2/3.6		
●	BKOC2574W	685360010755	277/240/208	1000/752/564	3.6/3.1/2.7		
●	BKOC2515W	685360010212	120	1250	10.4	60″	13.0 lbs
●	BKOC2505W	685360009971	208	1250	6.0		
●	BKOC2545W	685360010489	240/208	1250/940	5.2/4.5		
●	BKOC2575W	685360010793	277/240/208	1250/940/705	4.5/3.9/3.4		
●	BKOC2516W	685360010250	120	1500	12.6	72″	15.5 lbs
●	BKOC2506W	685360010014	208	1500	7.2		
●	BKOC2546W	685360010526	240/208	1500/1128	6.3/5.4		
●	BKOC2576W	685360010830	277/240/208	1500/1128/846	5.4/4.7/4.1		
●	BKOC2508W	685360010052	208	2000	9.6	96″	20 lbs
●	BKOC2548W	685360010564	240/208	2000/1504	8.3/7.2		
●	BKOC2578W	685360010878	277/240/208	2000/1504/1128	7.2/6.3/5.4		
●	BKOC25008W	685360009810	208	2500	12.0	96″	20 lbs
●	BKOC25408W	685360010328	240/208	2500/1880	10.4/8.7		
●	BKOC25708W	685360010632	277/240/208	2500/1880/1410	9.0/7.5/6.8		

SKU Legend: ◆ **= Popular Products;** ● **= Extended Offering** (Contact your local Marley Sales Representative for typically associated lead times)

Suggested Controls



TH114A240DBA



MS26 or M601W

Filler Sections:

CATALOG NO.	UPC	DESCRIPTION	SHIP WT.
FS12	098319731500	1 ft. Filler Section	2 lbs
FS24	098319731517	2 ft. Filler Section	4 lbs
FS36	098319731524	3 ft. Filler Section	6 lbs
FS48	098319731531	4 ft. Filler Section	8 lbs
FSJ2	098319731548	2 in. Joiner Strip	.5 lbs

Blank Sections:

CATALOG NO.	UPC	DESCRIPTION	SHIP WT.
BKOCBDA2W	685360009315	2.6 ft. Blank Section	4 lbs
BKOCBDA3W	685360009339	3 ft. Blank Section	5 lbs
BKOCBDA4W	685360009353	4 ft. Blank Section	7 lbs
BKOCBDA5W	685360009377	5 ft. Blank Section	9 lbs
BKOCBDA6W	685360009391	6 ft. Blank Section	11 lbs
BKOCBDA8W	685360009414	8 ft. Blank Section	14 lbs

Optional Controls & Accessories:

CATALOG NO.	UPC	DESCRIPTION	SHIP WT.
TA1AW	098319730411	SP Thermostat, rated 22A @ 120–277V	1 lbs
TA1TPAW	685360185996	Tamper-Resistant Version of TA1AW	1 lbs
TA2AW	685360186009	DP Thermostat, rated 22A @ 120–277V	1 lbs
TA2TPAW	098319730442	Tamper-Resistant Version of TA2AW	1 lbs
HCA2415/20W	098319730466	240V Load Transfer Switch, 20A	1 lbs
HCA1215/20W	098319730459	120V Load Transfer Switch, 20A	1 lbs
RSA1224	098319714800	120V/24V Transformer Relay, 22A	1 lbs
RSA2024	098319714855	208V/24V Transformer Relay, 22A	1 lbs
RSA2424	098319714909	240V/24V Transformer Relay, 22A	1 lbs
RSA2724	098319714954	277V/24V Transformer Relay, 19A	1 lbs
RA1W	098319730473	120V Duplex Receptacle	1 lbs
DSW2W	685360165066	Double-Pole Power On/Off Switch rated 20A @ 120–277V	1 lbs
PR24	098319713674	Single-Pole Power Relay, 24VControl rated 30A @ 120–240V, 23A @ 277V	1 lbs
PR120	098319713681	Same as PR24 except with 120V Control	1 lbs
ICANW	685360011097	Inside Corner	1 lbs
RA1COMPW	098319730480	Duplex Receptacle Cover only — carton of 10	1 lbs

NOTE: For high-altitude baseboard heater (mounted above 7,500 ft.), add suffix "H" to catalog number. 8 ft. length baseboards must be ordered in multiples of two pieces for shipment.

Dimensions and Clearances:

