Marley Industrial Products

DIRECT DRIVE MAN-COOLERS


Low Stand


Medium Stand


High Stand

- Rugged, heavy duty 18" to 48" cooling fans,
- Available with totally enclosed or explosion proof motors
- Non-sparking, cast aluminum props
- 14 Gauge steel body
- Enamel coating standard, optional acid resistant coating
- Manual starter switches available
- 360° Swivel on high and medium stand units
- Meets Federal OSHA requirements
- 1 Year Limited Warranty

FAN SIZE	ORDER NUMBER* 115/230V 60HZ 1 PH.	ORDER NUMBER* 230/460V 60HZ 3 PH.	HP	RPM	0" SP CFM	DB @10'	WT.	LIST TE 1 PH.	LIST TE 3PH.	LIST EXP 1 PH.	LIST EXP 3PH.
HIGH STAND MODELS											
18	**18H141**	**18H143**	1/4	1725	3050	72	228	•	•	•	•
	24H141	**24H143**	1/4	1725	5200	78	255	•	•	•	•
	24H121	**24H123**	1/2	1725	6000	78	260	•	•	•	•
24	**24H341**	**24H343**	3/4	1200	7000	72	280	•	•	•	•
	24H11	**24H13**	1	1725	7400	80	270	•	•	•	•
	24H31	**24H33**	3	1725	10500	85	300	•	•	—	•
	30H121	**30H123**	1/2	1725	8000	84	281	•	•	•	•
	30H341	**30H343**	3/4	1200	9000	78	350	•	•	•	•
30	**30H1121**	**30H1123**	1 1/2	1725	11000	90	340	•	•	•	•
	30H21	**30H23**	2	1200	12000	82	365	•	•	—	•
	30H31	**30H33**	3	1725	13000	92	360	•	•	—	•
	36H1121	**36H1123**	1 1/2	1725	14850	86	420	•	•	•	•
36	**36H21**	**36H23**	2	1725	16000	86	420	•	•	•	•
	36H2A1	**36H2A3**	2	1200	14000	80	420	•	•	—	•
	—	**36H33**	3	1150	19000	82	425	—	•	—	•
42	—	**42H23**	2	1150	19500	84	565	—	•	—	•
	—	**42H53**	5	1150	27000	84	590	—	•	—	•
48	—	**48H7123**	7 1/2	1150	33000	103	875	—	•	—	•
MEDIUM STAND MODELS											
18	**18M141**	**18M143**	1/4	1725	3050	72	163	•	•	•	•
	24M141	**24M143**	1/4	1725	5200	78	165	•	•	•	•
	24M121	**24M123**	1/2	1725	6000	78	180	•	•	•	•
24	**24M341**	**24M343**	3/4	1200	7000	72	200	•	•	•	•
	24M11	**24M13**	1	1725	7400	80	190	•	•	•	•
	24M31	**24M33**	3	1725	10500	85	220	•	•	—	•
	30M121	**30M123**	1/2	1725	8000	84	201	•	•	•	•
	30M341	**30M343**	3/4	1200	9000	78	270	•	•	•	•
30	**30M1121**	**30M1123**	1 1/2	1725	11000	90	260	•	•	•	•
	30M21	**30M23**	2	1200	12000	82	285	•	•	—	•
	30M31	**30M33**	3	1725	13000	92	280	•	•	—	•
	36M1121	**36M1123**	1 1/2	1725	14850	86	320	•	•	•	•
36	**36M21**	**36M23**	2	1725	16000	86	325	•	•	•	•
	36M2A1	**36M2A3**	2	1200	14000	80	325	•	•	—	•
	—	**36M33**	3	1150	19000	82	350	—	•	—	•
42	—	**42M23**	2	1150	19500	84	415	—	•	—	•
	—	**42M53**	5	1150	27000	84	440	—	•	—	•
48	—	**48M7123**	7 1/2	1150	33000	103	745	—	•	—	•
LOW STAND MODELS											
18	**18L141**	**18L143**	1/4	1725	3050	72	103	•	•	•	•
	24L141	**24L143**	1/4	1725	5200	78	115	•	•	•	•
	24L121	**24L123**	1/2	1725	6000	78	120	•	•	•	•
24	**24L341**	**24L343**	3/4	1200	7000	72	140	•	•	•	•
	24L11	**24L13**	1	1725	7400	80	130	•	•	•	•
	24L31	**24L33**	3	1725	10500	85	160	•	•	—	•
	30L121	**30L123**	1/2	1725	8000	84	141	•	•	•	•
	30L341	**30L343**	3/4	1200	9000	78	210	•	•	•	•
30	**30L1121**	**30L1123**	1 1/2	1725	11000	90	200	•	•	•	•
	30L21	**30L23**	2	1200	12000	82	225	•	•	•	•
	30L31	**30L33**	3	1725	13000	92	220	•	•	—	•
	36L1121	**36L1123**	1 1/2	1725	14850	86	250	•	•	—	•
36	**36L21**	**36L23**	2	1725	16000	86	255	•	•	•	•
	36L2A1	**36L2A3**	2	1200	14000	80	255	•	•	•	•
	—	**36L33**	3	1150	19000	82	260	•	•	—	•
42	—	**42L23**	2	1150	19500	84	315	—	•	—	•
	—	**42L53**	5	1150	27000	84	340	—	•	—	•
48	—	**48L7123**	7 1/2	1150	33000	103	625	—	•	—	•

Optional Casters for Low & Medium Stand Man-coolers

- Factory installed
- 2 Fixed and 2 Swivel casters per model

* **NOTE:** When ordering Explosion Proof models, add EXP suffix to model number

Optional Accessories

ORDER NUMBER	FAN SIZE	WHEEL SIZE	SHIPPING WEIGHT
CAS18	18"- 30"	4"	10 lbs.
CAS48	36"- 48"	6"	14 lbs.

NOTE: When ordering explosion proof model add EXP. suffix to model number.