

LEADING EDGE®
A Marley Engineered Products Brand

LCHHD24O & LCHHD30O

PROJECT	ENGINEER	SUBMITTED BY
DATE	ARCHITECT	
SHEET OF	CONTRACTOR	





WALL MOUNT



27" ROUND PEDESTAL BASE AND FIXED PEDESTAL COLUMN

SPECIFICATIONS

- ☐ **Durable safety clutch-style oscillating mechanism**. Designed for pedestal or wall mount applications. Can be set to oscillate at 45˚ to 90˚ sweep, or be secured in a fixed position. Head assembly can be tilted 10˚ up or 10˚ down.
- ☐ 24" and 30" diameter.
- ☐ 2 Speed, 1/4 HP, single phase, 120 volt, totally enclosed, permanently lubricated ball bearings, built-in thermal overload protection, permanent split capacitor motor with pull chain switch.
- ☐ Rear dome design allows for servicing or replacement of switch or capacitor.
- ☐ Precision balanced aluminum blades.
- ☐ Powder paint coated guards meeting OSHA safety standards.
- ☐ cULus and cETLus listed.
- ☐ Meets federal OSHA standards.

OPTIONAL MOUNTS

☐ Adjustable Pedestal ☐ Wall*
☐ 27" Round Base

**All wall mounts come with secondary support cable.*

ITEM	QTY	MARK	MODEL NUMBER	BLADE SIZE	FAN STYLE	CFM		RPM		MOTOR H.P.	MAX AMPS	REMARKS
						HI	LOW	HI	LOW			

HEAVY-DUTY PREMIUM OSCILLATING AIR CIRCULATOR SUBMITTAL SHEET