Marley Industrial Products

SPECIALTY WASHDOWN AIR CIRCULATOR

This exclusive fan is ideally suited for comfort cooling in food and beverage processing facilities, greenhouses, poultry plants, amusement parks and other high humidity or washdown environments. Fan meets UL 507 spray test requirements.

LEADING EDGE®
A Marley Engineered Products Brand



LIMITED 2 YR WARRANTY

Washdown Air Circulator
Fan motor and all mounts on this page: Pedestal, Ceiling, I-Beam, Wall, and Suspension, are coated with FDA approved white epoxy (FDA 21 CFR 175.300), USDA approved for incidental food contact.

Fan Performance

Blade Size	Fan Head	Max Amps	CFM High	CFM Low
24”	LCHWD24	4.0	6,800	5,200
30”	LCHWD30	4.1	8,600	6,200

Motor	2-speed, 1/3 HP, 48-frame, single phase, 120 volt totally enclosed, permanently lubricated ball bearings, built-in thermal overload protection, permanent split capacitor motor.
Switch	5’ long air actuated pendant switch
Cord	5’ long 3 Conductor SJT type
Blade	Balanced aluminum
Guard	Zinc plated

Meets OSHA standards.
MEP recommends the use of safety cable model 2430SC with this fan when mounted on a wall, I-beam, ceiling mount.
Safety cable included with I-beam, ceiling and suspension mounts.

Ordering Summary

BLADE SIZE	FAN TYPE	ORDER NUMBER FAN HEAD	ORDER NUMBER MOUNT	SHIPPING WEIGHT HEAD	SHIPPING WEIGHT MOUNT
24”	Head	**LCHWD24**	**—**	42 lbs.	—
24”	Pedestal	**LCHWD24**	**LFPCBWD**	42 lbs.	35 lbs.
24”	Wall Mount	**LCHWD24**	**LWBWD**	42 lbs.	5 lbs.
24”	I-Beam Mount	**LCHWD24**	**LIBWD**	42 lbs.	8 lbs.
24”	Ceiling Mount	**LCHWD24**	**LCMWD**	42 lbs.	8 lbs.
30”	Head	**LCHWD30**	**—**	49 lbs.	—
30”	Pedestal	**LCHWD30**	**LFPCBWD**	49 lbs.	35 lbs.
30”	Wall Mount	**LCHWD30**	**LWBWD**	49 lbs.	5 lbs.
30”	I-Beam Mount	**LCHWD30**	**LIBWD**	49 lbs.	8 lbs.
30”	Ceiling Mount	**LCHWD30**	**LCMWD**	49 lbs.	8 lbs.

Note: LCHWD30 Fan head does not meet UPS shipping criteria.