Marley
Industrial Products

PROJECT	ENGINEER	SUBMITTED BY
DATE	ARCHITECT	
SHEET OF	CONTRACTOR	



Specifications:

> 115v, single phase, totally enclosed, permanently lubricated 2 or 3 speed motor.
> Precision balanced aluminum blades with heavy gauge steel spider and hub.
> Powder paint coated rear guard meets federal OSHA standards.
> Conveniently located rotary speed control.
> 18 gauge steel die formed venturi / mounting plate with rust resistant powder paint coating.
> Aluminum unit mounted shutter included on LPES models. Eliminates inside / outside framing.

ORDER NUMBER	TYPE	BLADE SIZE	OUTSIDE DIMENSION	CFM AT 115V HIGH	CFM AT 115V MED	CFM AT 115V LOW	AMPS (HIGH)	SHIP WT. LBS.
LPE12V	VENTURI	12”	17-3/4” Sq.	2000	1600	1150	1.1	14
LPE16V	VENTURI	16”	21” Sq.	3000	2650	2250	1.1	21
LPE22V	VENTURI	22”	27-1/2” Sq.	4200	—	3700	2.1	37
LPE12S	SHUTTER	12”	15” Sq.	2000	1600	1150	1.1	16
LPE16S	SHUTTER	16”	19” Sq.	3000	2650	2250	1.1	25
LPE24S	SHUTTER	24”	27” Sq.	5000	—	4200	2.2	44
LPE30S	SHUTTER	30”	33” Sq.	7800	—	6600	2.5	51

ITEM	QUANTITY	MARK	MODEL NUMBER	FAN TYPE	BLADE SIZE	OUTSIDE DIMENSION	CFM @ 115V HIGH	CFM @ 115V MED	CFM @ 115V LOW	AMPS (HIGH)	SHIP WT (LBS)