
PERMANENT MOUNT BLOWER





- 18” to 36” Direct drive blowers available with one way or two way swivel
- Mount to overhead beams or wall columns
- Available with totally enclosed or explosion proof motors
- Non-sparking, cast aluminum blades
- 14 Gauge steel body, steel tubing yoke
- Front and rear spiral guards
- Meets Federal OSHA requirements
- 1 Year Limited Warranty

1 Way Swivel

BLADE DIA.	1-PHASE 115/230V ORDER NO.	3-PHASE 230/460V ORDER NO.	NO. OF BLADES	HP	RPM	0 " SP CFM	DB @ 10 '	WT.	LIST TE 1 PH.	LIST TE 3 PH.	LIST EXP 1 PH.	LIST EXP 3 PH.
18	**18S141**	**18S143**	4	1/4	1725	3050	72	163	•	•	•	•
24	**24S141**	**24S143**	2	1/4	1725	5200	78	165	•	•	•	•
	24S121	**24S123**	4	1/2	1725	6000	78	180	•	•	•	•
	24S341	**24S343**	6	3/4	1200	7000	72	200	•	•	•	•
	24S11	**24S13**	6	1	1725	7400	80	190	•	•	•	•
	24S31	**24S33**	6	3	1725	10500	85	220	•	•	–	•
30	**30S121**	**30S123**	4	1/2	1725	8000	84	201	•	•	•	•
	30S341	**30S343**	6	3/4	1200	9000	78	270	•	•	•	•
	30S1121	**30S1123**	6	1 1/2	1725	11000	90	260	•	•	•	•
	30S21	**30S23**	6	2	1200	12000	82	285	•	•	–	•
	30S31	**30S33**	2	3	1725	13000	92	280	•	•	–	•
36	**36S1121**	**36S1123**	2	1 1/2	1725	14850	86	320	•	•	•	•
	36S21	**36S23**	4	2	1725	16000	86	325	•	•	•	•
	36S2A1	**36S2A3**	6	2	1200	14000	80	325	•	•	–	•
	—	**36S33**	3	3	1150	19000	82	350	–	•	–	•

2 Way Swivel

BLADE DIA.	1-PHASE 115/230V ORDER NO.	3-PHASE 230/460V ORDER NO.	NO. OF BLADES	HP	RPM	0 " SP CFM	DB @ 10 '	WT.	LIST TE 1 PH.	LIST TE 3 PH.	LIST EXP 1 PH.	LIST EXP 3 PH.
18	**18D141**	**18D143**	4	1/4	1725	3050	72	163	•	•	•	•
24	**24D141**	**24D143**	2	1/4	1725	5200	78	165	•	•	•	•
	24D121	**24D123**	4	1/2	1725	6000	78	180	•	•	•	•
	24D341	**24D343**	6	3/4	1200	7000	72	200	•	•	•	•
	24D11	**24D13**	6	1	1725	7400	80	190	•	•	•	•
	24D31	**24D33**	6	3	1725	10500	85	220	•	•	–	•
30	**30D121**	**30D123**	4	1/2	1725	8000	84	201	•	•	•	•
	30D341	**30D343**	6	3/4	1200	9000	78	270	•	•	•	•
	30D1 121	**30D1 123**	6	1 1/2	1725	11000	90	260	•	•	•	•
	30D21	**30D23**	6	2	1200	12000	82	285	•	•	–	•
	30D31	**30D33**	2	3	1725	13000	92	280	•	•	–	•
36	**36D1 121**	**36D1 123**	2	1 1/2	1725	14850	86	320	•	•	•	•
	36D21	**36D23**	4	2	1725	16000	86	325	•	•	•	•
	36D2A1	**36D2A3**	6	2	1200	14000	80	325	•	•	–	•
	—	**36D33**	3	3	1150	19000	82	350	–	•	–	•

NOTE: When ordering explosion proof model add exp. suffix to model number.