# SSARWH ARCHITECTURAL SMARTSERIES®
## Programmable Wall Heater






### *Technical Specifications*:

**Temp Range**: 40°–90°F
**CFM**: 100

### *Ideal Spaces*:

Living Rooms
Basements
Lobbies
Offices
Conference Rooms
Waiting Room
Vestibules & Stairwells
Restaurants

White Aluminum

- The best in contemporary design with a hidden digital. touch screen LED thermostat (5/2-day programming)
- Rugged heavy duty die cast aluminum grille, BMS compatible—Connects to Building Management Systems for optimum control
- Energy efficiency with proportional heating that automatically adjusts wattage output
- Maintains heat within 1.5 degree of set temperature (as compared to five degrees with conventional bi-metal thermostats)
- Hold function maintains constant set temperature. Use for freeze protection or vacation setting when away
- Lockout Feature—Securely maintain comfort levels
- 'Right out of the box' installation; fits recessed between standard studs walls with two-piece construction
- No ducting or plumbing needed means no heat loss before the heat enters the room
- Power on/off switch for added safety during maintenance

Intertek

SMART ENERGY SAVER
Saves up to 40%* energy usage

5 YEAR WARRANTY ELEMENT

1 YEAR WARRANTY WORKMANSHIP

# SSARWH ARCHITECTURAL SMARTSERIES®
## Programmable Wall Heater

**Scan the QR code to access additional specs and features**

### *Models & Specifications:*

| ITEM INFORMATION | | | ELECTRICAL DATA | | | | | |
|---|---|---|---|---|---|---|---|---|
| | CATALOG NO. | UPC | VOLTS | PHASES | WATTS | AMPS | BTU/HR. | SHIP WT. |
| ◆ | SSARWH1802 | 685360156842 | 120 | 1 | 900/1800 | 15 | 6,142 | 25 lbs |
| ◆ | SSARWH4808 | 685360156767 | 208 | 1 | 1440/4800 | 23.1 | 16,378 | 25 lbs |
| ◆ | SSARWH4804 | 685360156774 | 240 | 1 | 1440/4800 | 20 | 16,378 | 25 lbs |
| ◆ | SSARWH4807 | 685360156804 | 277 | 1 | 1440/4800 | 17.3 | 16,378 | 25 lbs |

**SKU Legend:** ◆ **= Popular Products;** ● **= Extended Offering** (Contact your local Marley Sales Representative for typically associated lead times)

NOTE: For handling 208V Max AMP loads, contact your local Marley Sales Representative. Standard grille color is White. Add AL (Aluminum) suffix to catalog number of both the heater and mounting frame (ex. SSAR1802AL).
Mounting Limitations: Do not install heater closer than 12 in. to the floor, 12 in. to an adjacent wall, 36 in. to the ceiling. Do not install heater behind towel rack or door, upside down or sideways, in the floor, in the ceiling, or in closets.

### *Optional Accessories:*

| CATALOG NO. | UPC | DESCRIPTION | COLOR | SHIP WT. |
|---|---|---|---|---|
| HTWHSM | 685360155456 | Surface Mounting Frame 15 ⅜" W x 19 ³⁄₁₆" H x 3 ¾" D | White | 4 lbs |
| HTWHS1 | 685360155487 | 1 in. Semi-Recess Mounting Frame 15 ⅜" W x 19 ³⁄₁₆" H x 1" D | White | 4 lbs |
| HTWHS2 | 685360155517 | 2 in. Semi-Recess Mounting Frame 15 ⅜" W x 19 ³⁄₁₆" H x 2" D | White | 4 lbs |

### *Dimensions and Clearances:*







