
470 Beauty Spot Rd. E, Bennettsville, SC 29512 USA

SUBMITTAL SHEET
UCJ SERIES
INSTITUTIONAL
CONVECTOR

UCJ SERIES - INSTITUTIONAL CONVECTOR

CAPACITIES
500, 750, 1000, 1250, 1500, Watts 120, 208, 240, 277V 1Ø only



See Selection Chart
Back Page

c UL us

JOB NAME: _____

LOCATION: _____

ARCHITECT: _____

ENGINEER: _____

CONTRACTOR: _____

SUBMITTED BY: _____

DATE: _____

QTY.	CATALOG NUMBER	TAG	HEATER			AMPS	CONTROL VOLTS	BUILT-IN CONTROLS
			KW	VOLTS	Ø			

UCJ SERIES

BERKO®

470 Beauty Spot Rd. E, Bennettsville, SC 29512 USA

SELECTION CHART

CATALOG NUMBER	HEATER VOLTS	WATTS (KW)	AMPS	WT. (LBS.)
UCJ400	120	400	3.3	38
UCJ408	208		1.9	
UCJ404	240		1.7	
UCJ407	277		1.4	
UCJ500	120	500	4.2	43
UCJ508	208		2.4	
UCJ504	240		2.2	
UCJ507	277		1.8	
UCJ750	120	750	6.2	53
UCJ758	208		3.6	
UCJ754	240		3.3	
UCJ757	277		2.7	
UCJ753	347		2.2	
UCJ1000	208	1000	8.3	63
UCJ1008	208		4.8	
UCJ1004	240		4.4	
UCJ1007	277		3.6	
UCJ1003	347		2.9	
UCJ1006	600		1.7	
UCJ1250	120	1250	10.4	78
UCJ1258	208		6.0	
UCJ1254	240		5.4	
UCJ1257	277		4.5	
UCJ1253	347		3.6	
UCJ1256	600		2.1	
UCJ1500	120	1500	12.5	93
UCJ1508	208		7.2	
UCJ1504	240		6.5	
UCJ1507	277		5.4	
UCJ1503	347		4.3	
UCJ1506	600		2.5	
UCJ2008	208	2000	9.6	128
UCJ2004	240		8.8	
UCJ2007	277		7.2	
UCJ2003	347		5.8	
UCJ2006	600		3.3	

APPLICATIONS

UCJ Series type convector is designed as an institutional unit with low operating temperatures and is U.L. listed. This is a rugged, wall mounted, tamper proof convection heater designed to provide heat in correctional or rehabilitational institutions where safety is a major concern.

FEATURES

- 140° F maximum surface temperature in a 70° ambient means the unit is ideal for applications that require a low-operating temperature below that of most commercial convectors.
- Internal tamper proof thermostat with 55° to 100° F range allows for temperature control of the unit with a high degree of security.
- 12 gauge perforated steel, sloped top cover makes the unit rugged and resistant to any attempted vandalism.
- A built-in double pole power on/off switch that is accessible without the removal of any covers results in a convenient means of disconnecting power to the unit for servicing and cleaning.
- A durable, baked enamel finish insures that the unit will resist chipping, cracking, or rusting throughout the life of the unit.

DIMENSIONS

WATTAGE	LENGTH	HEIGHT	DEPTH
400	24”	16”	5”
500	28”	16”	5”
750	36”	16”	5”
1000	48”	16”	5”
1250	60”	16”	5”
1500	72”	16”	5”
2000	96”	16”	5”

