Marley Industrial Products

HEAVY DUTY BELT DRIVE EXHAUST FAN



- Available with totally enclosed or explosion proof motor
- Standard props are heavy gauge steel
- Cast aluminum props available for explosion proof requirements
- Heavy 14 gauge steel panel with welded steel pipe bracing
- Cast iron ball bearings in pillow blocks with cast iron sheaves
- Options available: Reverse flow for supply, and acid resistant coating — Call factory
- Guards: Front and rear box available
- Industrial grey enamel finish
- Fans delivered completely assembled, factory tested and adjusted, ready to install
- A special motorized shutter to be used with supply fan, Model WSHM, when shutter is mounted directly in front of fan
- Venturi can also be reversed when flat front surface desired — Request when ordering fan

Dimensions

FAN SIZE	A	B	C
24”	24	30	16
30”	30	36	16
36”	36	42	19
42”	42	48	20
48”	48	54	21
60”	60	66	28





A — Blade Diameter
B — Panel Size
C — Depth Dimension
“C” Depth dimension varies with motor selection.

Ordering Summary

FAN DIA.	1-PHASE 115/230V MODEL NO.	3-PHASE 208-230/460V MODEL NO.	PANEL SIZE SQ.	HP	RPM	CFM 0” SP	DB @ 10’	APPROX WT.	LIST TE 1 PH.	LIST TE 3 PH.	LIST EXP 1 PH.	LIST EXP 3 PH.
	WEB24G	**WEB24G3**		¼	700	5200	60	100	•	•	•	•
	WEB24H	**WEB24H3**		⅓	775	5760	63	100	•	•	•	•
24”	**WEB24I**	**WEB24I3**	30”	½	885	6575	66	130	•	•	•	•
	WEB 24J	**WEB24J3**		¾	1015	7545	71	140	•	•	•	•
	WEB24K	**WEB24K3**		1	1110	7800	73	140	•	•	•	•
	WEB30G	**WEB30G3**		¼	460	7160	61	140	•	•	•	•
	WEB30H	**WEB30H3**		⅓	505	7860	63	150	•	•	•	•
30”	**WEB30I**	**WEB30I3**	36”	½	580	8500	64	158	•	•	•	•
	WEB30J	**WEB30J3**		¾	660	10200	66	168	•	•	•	•
	WEB30K	**WEB30K3**		1	725	11300	70	168	•	•	•	•
	WEB30L	**WEB30L3**		1 ½	820	12765	77	178	•	•	•	•
	WEB36H	**WEB36H3**		⅓	385	9110	64	185	•	•	•	•
	WEB36I	**WEB36I3**		½	440	10405	66	190	•	•	•	•
36”	**WEB36J**	**WEB36J3**	42”	¾	505	11945	68	200	•	•	•	•
	WEB36K	**WEB36K3**		1	555	13125	70	200	•	•	•	•
	WEB36L	**WEB36L3**		1 ½	625	14300	72	210	•	•	•	•
	WEB36M	**WEB36M3**		2	690	16500	74	230	•	•	•	•
	WEB42H	**WEB42H3**		⅓	320	11375	64	205	•	•	•	•
	WEB42I	**WEB42I3**		½	365	12980	65	215	•	•	•	•
42”	**WEB42J**	**WEB42J3**	48”	¾	420	14930	67	225	•	•	•	•
	WEB42K	**WEB42K3**		1	455	16180	69	235	•	•	•	•
	WEB42L	**WEB42L3**		1 ½	515	18310	71	240	•	•	•	•
	WEB42M	**WEB42M3**		2	570	20265	74	245	•	•	•	•
	—	**WEB42P3**		3	650	23100	79	265	–	•	–	•
	WEB48I	**WEB48I3**		½	295	15200	69	190	•	•	•	•
	WEB48J	**WEB48J3**		¾	335	17300	70	195	•	•	•	•
48”	**WEB48K**	**WEB48K3**	54”	1	370	19100	71	205	•	•	•	•
	WEB48L	**WEB48L3**		1 ½	415	21700	72	255	•	•	•	•
	WEB48M	**WEB48M3**		2	455	24200	74	280	•	•	•	•
	—	**WEB48P3**		3	525	28100	80	305	–	•	–	•
	—	**WEB48T3**		5	620	33100	83	315	–	•	–	•
	WEB60K	**WEB60K3**		1	265	24050	76	370	•	•	•	•
	WEB60L	**WEB60L3**		1 ½	300	27225	77	380	•	•	•	•
60”	**WEB60M**	**WEB60M3**	66”	2	390	32200	78	390	•	•	•	•
	—	**WEB60P3**		3	450	37100	84	405	–	•	–	•
	—	**WEB60T3**		5	540	44600	86	425	–	•	–	•

NOTE: When ordering Explosion Proof models, add EXP suffix to model number

All units are made to order and are not returnable.