PROJECT: _____ **ITEM NO.:** _____

CONTROL CENTER MODEL CC-101

AUTOMATIC REVERSING ACTION

SPECIFICATIONS

STAINLESS STEEL ENCLOSURE
- NEMA 4
- Stainless steel construction
- Easy to clean and keep clean

AUTOMATIC REVERSING CONTROL
- Reverses direction of motor at each startup
- Increases cutting element life and reduces jams

REVERSING DELAY
- Disposer will not reverse while motor is in motion
- Protects motor from burn out from operator misuse

AUTOMATIC DROP OUT SYSTEM
- If a power loss occurs, control will automatically disengage power lines
- Disposer must be restarted

DISCONNECT SWITCH
- Disconnects electrical power beyond switch for service
- Interlock with front cover

SOLID STATE CONTROL
- Operates on 24V

SOLID STATE CONTROL CIRCUIT
- Printed circuit board with control diagnostic/function lights, delay timers and timed run pin and reversing control

POST WATER FLUSH
- Adjustable timer allows water to run automatically for up to 10 minutes, flushing disposer and drain lines after disposer is shut off

TIMED RUN OR CONTINUOUS RUN
- Selected at your discretion, simply by moving the plug-in in on the printed circuit board
- Timed run shuts off disposer automatically after 10 minutes
- Can be shut off manually any time

SOLENOID VALVE
- Packed unattached inside control center carton
- Ensures that water is flowing into disposer while disposer is operating



1 YEAR ON-SITE PARTS & LABOR WARRANTY

DIMENSIONS



VOLTAGE/PHASE AVAILABILITY

Model	Voltage/Hz	Phase	Disposer Models
CC101K-5	120V, 50/60 Hz	1 Ph	SS-100 to SS-200
CC101K-6	208-240V, 50/60 Hz	1 Ph	SS-100 to SS-200
CC101K-7	208-240V, 50/60 Hz	3 Ph	SS-100 to SS-1000
CC101K-8	380-460V, 50/60 Hz	3 Ph	SS-100 to SS-1000

A complete collection of our product drawings is available for download at the **InSinkErator Revit/CAD** Library, which can be found at www.insinkerator.com/foodservice. Product information is also accessible on ***The KCL CADalog***. More information is available from KCL at www.kclcad.com.

1250 International Drive
Mount Pleasant, WI 53177
TEL: 800-845-8345
www.insinkerator.com/foodservice

c UL us LISTED ISO 9001 QUALITY SYSTEMS CERTIFIED

InSinkErator ©2023 Printed in USA

RECOMMENDED INSTALLATION



NOTE: The CC-101 control center should be mounted 1-1/2" (38.1 mm) back from the front surface of the table.