HBB SERIES
Electric Hydronic Baseboard Heater





Ideal Spaces:

Bedrooms
Living/Family Room
Basements
Offices
Conference Rooms
Waiting Rooms
Entrance Ways

Beige

- Ideal for superior, efficient and zoned Primary/Secondary comfort
- Low profile ideal for limited wall space
- Storage fluid maximizes convection, minimizing air flow, reducing flow of bacteria and dust
- Large element reservoir maximizes the volume of heat storage fluid for prolonged comfort
- Gentle heat continues to radiate even after the thermostat turns off due to the hydronic element retention qualities
- Hydronic element reduces on/off cycling of thermostat maintaining even room comfort and reducing energy costs
- Low surface temperatures safe for installations with pets, children and carpet
- Heavy-duty welded steel louvered grilles discourage insertion of foreign objects
- Built-in wire way, lead wires, and knockouts allow quick field connection from either end
- UL-listed for installation flush to any wall and flat on any floor type; pre-notched marks for mounting guide
- High temperature safety limit
- Corrosion resistant aluminum fins are pressure-fitted to copper tubing to assure rapid heat transfer, air flow
- Air flow is directed away from walls and into the room to help prevent wall streaking & minimizes dry air

c UL us

10 YEAR WARRANTY ELEMENT

1 YEAR WARRANTY WORKMANSHIP

QMARK
A Marley Engineered Products Brand

HBB SERIES
Electric Hydronic Baseboard Heater

Scan the QR code to access additional specs and features

Models & Specifications:

	ITEM INFORMATION		ELECTRICAL DATA			DIMENSIONAL DATA	
	CATALOG NO.	UPC	VOLTS	WATTS	AMPS	LENGTH	SHIP WT.
◆	HBB504	68536035789	240/208	500/375	2.1/1.8	28″	10 lbs
◆	HBB754	68536035826	240/208	750/563	3.1/2.7	34″	12 lbs
◆	HBB1004	68536035635	240/208	1000/750	4.2/3.6	46″	15 lbs
◆	HBB1254	68536035673	240/208	1250/938	5.2/4.5	58″	19 lbs
◆	HBB1504	68536035710	240/208	1500/1125	6.3/5.8	70″	22 lbs
◆	HBB2004	68536035741	240/208	2000/1500	8.3/7.2	94″	30 lbs
●	HBB500	68536035772	120	500	4.2	28″	10 lbs
●	HBB508	68536035802	208	500	2.4	28″	10 lbs
●	HBB750	68536035819	120	750	6.3	34″	12 lbs
●	HBB758	68536035840	208	750	3.6	34″	12 lbs
●	HBB1000	68536035628	120	1000	8.3	46″	15 lbs
●	HBB1008	68536035659	208	1000	4.8	46″	15 lbs
●	HBB1250	68536035666	120	1250	10.4	58″	19 lbs
●	HBB1258	68536035697	208	1250	6	58″	19 lbs
●	HBB1500	68536035703	120	1500	12.5	70″	22 lbs
●	HBB1508	68536035734	208	1500	7.2	70″	22 lbs
●	HBB2008	68536035765	208	2000	9.6	94″	30 lbs

SKU Legend: ◆ **= Popular Products** ● **= Extended Offering** (Contact your local Marley Sales Representative for typically associated lead times)

Optional Accessories:

CATALOG NO.	UPC	DESCRIPTION	SHIP WT.*
HBBT1	685360035574	25 amp @ 120-277 VAC; Single-Pole Thermostat Snap-Action Type; Field-Installed in Junction Box	1 lbs
HBBT2	685360035598	25 amp @ 120-277 VAC; Double-Pole Thermostat Snap-Action Type; Field-Installed in Junction Box	1 lbs
HBBT1TP	685360035581	Same as Model HBBT1 except Tamper-Resistant	1 lbs
HBBT2TP	685360035604	Same as Model HBBT2 except Tamper-Resistant	1 lbs
HBBAC*	685360035383	Air Conditioner Outlet Section, 20 amps @ 208/240 VAC	2 lbs
HBBDR	685360035420	Duplex Receptacle Section, 15 amps @ 120 VAC	2 lbs
HBBDSDR120	685360147970	Double-Pole Disconnect Switch /120V Receptacle	3 lbs
HBBWS	685360035611	8 in. Blank Wiring Section	1 lbs
HBBLVR0*	685360035475	Low Voltage Relay Control Section, 22 amps @ 120 VAC	3 lbs
HBBLVR8*	685360035505	Low Voltage Relay Control Section, 22 amps @ 208 VAC	3 lbs
HBBLVR4*	685360035482	Low Voltage Relay Control Section, 22 amps @ 240 VAC	3 lbs
HBBCDS2	685360035390	Double-Pole Power On/Off Switch Section	2 lbs
CBDCIC*	685360014609	Inside Corner	1 lbs
CBDCOC*	685360014616	Outside Corner	1 lbs

*HBBAC - HBBDR - HBBLVR - HBBWS accessories add 8 in. to baseboard length.

HBBT1 & HBBT2

HBB1TP & HBB2TP



*HBBAC



*HBBDR



*HBBLVR

*Add 8″ to length of installation

Dimensions and Clearances:



SIDE VIEW



Length varies with model.
See selection chart.





CONTROL SECTION